

TECNI CERA MICA

**PRESTACIONES DECLARADAS
DECLARED PERFORMANCES**

| Características esenciales Essential characteristics | Prestaciones | Especificación técnica armonizada |
|--|--------------------|--------------------------------------|
| Reaccion al fuego Reaction to fire | Clase/ Class A1 | EN14411:2012 |
| Emision de sustancias peligrosas Relased of dangerous substance , for | | |
| Cadmio/Cadmium Plomo / Lead | NPD NPD | |
| Adhesivo cementoso / Cementitious Adhesive Tipo C1 / Type C1 | >0,5 N/mm2 | |
| Durabilidad para Durability for | | |
| Usos interiores Internal used | Cumple Pass | |

Las prestaciones del producto son conformes cib kas orestacuibes declaradas
The performance of the product is in conformity with the declared performance
La presente declaracion de prestacines se emite bajo la única responsabilidad del fabricante
This declaration of performance is issued under the sole responsibility of the manufacturer

**Firmado por y en nonmbre del fabricante por:
Signed for and on behalf of the manufacturer by:
Director General / Managing Director:**

L'Alcora , Castellon 16 octubre 2018

Eduardo Hernandez
TECNICERAMICA, S.A.
C.I.F.: A-12421962
Ctra. Ribesalbes, s/n - Apdo. Correos 28
Tel. 964 38 11 77 - Fax: 964 38 60 43
12110 ALCORCA (Castellón)



EC Declaration of Conformity



The undersigned, representing the following manufacturer

TECNICERAMICA, S.A.
CTRA. RIBESALBES, S/N
12110- ALCORA- CASTELLON (ESPAÑA)

Manufacturing plant : ALCORA –CASTELLON - ESPAÑA

Herewith declare:

That the product **“Wall tile, 30x30 Series”**, is in conformity with the provisions of **Annex ZA – Bill Group to UNE EN 14411** Ceramic tiles – Definitions, classification, characteristics and marking – Dust pressed ceramic tiles E > 10 %

Description and intended use of the product: Ceramic walls tiles, glazed, for internal wall finishes.

Provisions to which the product conform:

| Characteristics | Declared value | Reports and notes |
|---|--|-------------------------------------|
| Reaction to fire Flexural tensile strength | NPD Breaking strength 1072 N Modulus of rupture >12 N/mm ² (24 N/mm ²) NPD (not intended for suspended ceilings) | Not intended for suspended ceilings |
| Bond strength / adhesion | NPD | |
| Release of dangerous substances | NPD | |

Name and address of notified laboratories involved:

Laboratorio Ceramico Sebastián Carpi. Col. Ing. Industriales. Castellon. España.

Notified under registration number 15/LE064.

LGAI Technological Center. Campus de la UAB. Bellaterra. Barcelona. España.

Notified under registration number 9/LE902

Signature:

TECNICERAMICA, S.A.

C.I.F.: A-12421002

Ctra. Ribesalbes, s/n - Apdo. Correos 23

Tel. 964 38 11 77 - Fax: 964 38 60 43

12110 ALCORA (Castellón)

Name: Eduardo Hernandez

Position: Managing Director.

Date: 16/10/2018