

ELYSSA TRADING

24 rue Domer 69007 LYON
Tel : 03 83 20 30 84 Fax : 03 83 31 19 97
Mail : elyssa-trading@orange.fr

DECLARATION OF PERFORMANCE **No. 001SCR2013-06-25**

1. Unique identification code of the product type:

Dry-pressed ceramic tiles,with water absorption $E_b > 10 \%$

2.Intended use(s):

For internal walls and floorings.

3.Name or registered trade mark,and contact address of the manufacturer:

EIYSSA-TRADING 24 Rue Domer LYON

5. Name and identification number of notified laboratory,if relevant :

Non applicable

6. AVCP SYSTEM:

System 4

ELYSSA TRADING

24 rue Domer 69007 LYON

Tel : 03 83 20 30 84

Fax : 03 83 31 19 97

Mail : elyssa-trading@orange.fr

7. Declared performances :

Essential characteristics	performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2012
Release of dangerous substance,for		
-Cadmium	NPD	
-Plomb	NPD	
Breaking strength	NPD Non, le module de rupture doit être indiqué conformément à la EN 14411 Epaisseur ≥7,5 mm : minimum 12 N/mm² Epaisseur < 7,5 mm : minimum 15 N/mm²	
Cementitious adhesive type C2	0.5 N/ mm ²	
Thermal shock resistance	Confirme	
Durability for :		
Internal use	Confirme	

ELYSSA TRADING

24 rue Damer 69007 LYON

Tel : 03 83 20 30 84

Fax : 03 83 31 19 97

Mail : elyssa-trading@orange.fr

8. The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

ELYSSA TRADING

24 rue Domer 69007 LYON
Tel : 03 83 20 30 84 Fax : 03 83 31 19 97
Mail : elyssa-trading@orange.fr

CE

ELYSSA TRADING
24 street Domer LYON
Elyssa-trading@orange.fr
05
001SCR2013-06-25

EN 14411:2012

Dry-pressed ceramic tiles,with water absorption

$E_b > 10 \%$

For internal walls and floorings.

Reaction to fire	A1
Cementitious adhesive type C2	0.5 N/ mm ²
Thermal shock resistance	Confirme
Durability for :	
Internal use	Confirme